





Great Basin™ Quick Reference Guide



 = GB-Series Specifications **(-LO Suffix)** = Low Profile PATG-Series Unit

***** = If GB-15, GB-20, and GB-25 are buried flush at floor and w/o riser, cover load is 450 lbs.
(All models are certified to ASME A112.14.3 and Listed by IAPMO except GB-125)

Great Features and More Cost Competitive

SPECIFICATIONS

SCHIER MODEL		Capacity				Pipe Sizes			Rough-in Dimensions (In.)								Cover		Weight (lbs.)	
		Flow Rate (GPM)	Grease (Lbs.)	Liquid (Gal.)	Solids (Gal.)	Plain End SCH. 40		Optional Male Thread (No Charge)	Body			Inlet / (GB)Outlet			PATG-Series Outlet			Load Rating (lbs.)	Dry	Wet
						Standard	Optional (NO Charge)		L	W	H	A	B	C	D	E				
PATG-1412	10	20	5.3	—	2"	3"	2, 3"	17-1/2	15-1/4	15	8-3/8	6-5/8	10-1/4	4-3/4	6	500	20	64		
PATG-1815 GB-15	15	60	74	2	2"	3"	2, 3"	23-1/2	15-1/4	18-1/2	11	7-1/2	13-1/2	5	6	500	30	113		
PATG-15-LO GB-15	15	60	74	2	2"	3"	2, 3"	24-1/2	18-1/2	10-3/4	6	4-3/4	7-1/2	3-1/4	5-3/4	500	35	118		
PATG-1820 GB-20	20	70	109	2	2"	3"	2, 3"	25-1/4	19-1/4	19-1/4	12	7-1/4	14-1/4	5	6-1/4	500	37	179		
PATG-20-LO GB-20	20	80	109	2	2"	3"	2, 3"	30-1/2	24-1/2	13-3/4	6-1/2	7-1/4	10-1/4	3-1/2	5-3/4	500	50	225		
PATG-2025 GB-25	25	98	75	2	3"	2"	2, 3"	29-3/4	23-1/2	23-1/4	13	10-1/4	16	7-1/4	6-7/8	500	63	297		
PATG-2420	30	109	31	—	3"	2"	2, 3"	29-3/4	23-1/2	23-1/4	14-1/2	8-3/4	17-7/8	5-3/8	6-7/8	500	63	322		
PATG-30-LO	30	90	23	—	3"	2"	2, 3"	34-1/2	24-1/2	13-3/4	6-1/2	7-1/4	10-1/4	3-1/2	5-3/4	500	55	322		
PATG-2635 GB-35	35	120	142	6	3"	4"	3, 4"	29-3/4	23-1/2	28-1/2	16-1/2	12	21	7-1/2	6-7/8	500	75	247		
PATG-35-LO GB-35	35	98	142	6	3"	2"	2, 3"	40-1/2	24-1/2	13-3/4	6-1/2	7-1/4	10-1/4	3-1/2	5-3/4	500	65	409		
PATG-2824	40	180	54	—	4"	3"	3, 4"	31-1/4	26	32-1/2	21-1/2	11	25-3/4	6-3/4	6-7/8	500	82	298		
PATG-3050 GB-50	50	259	249	6	4"	3"	3, 4"	35-1/4	26	32-1/2	21-1/2	11	25-3/4	6-3/4	6-7/8	500	94	532		
PATG-50-LO GB-50	50	128	249	6	3"	4"	3, 4"	54	24-3/4	16-1/4	6-3/4	9-1/2	11	5-1/4	12	500	70	594		
PATG-3224	60	288	67	—	4"	3"	3, 4"	38-3/4	26	32-1/2	21-1/2	11	25-3/4	6-3/4	6-7/8	500	105	322		
PATG-3475 GB-75	75	300	616	15	4"	3"	3, 4"	39	28-1/2	32-1/2	22	10-1/2	26-1/4	6-1/4	6-7/8	500	105	1,171		
PATG-3628 GB-250	100	350	1,076	15	4"	3"	3, 4"	41-1/4	35-1/2	32-1/2	22	10-1/2	26-1/4	6-1/4	6-7/8	500	162	2,313		